

PRODUCT RANGE



Head Office and Production Germany
WIWA Wilhelm Wagner GmbH & Co. KG

Gewerbestrasse 1-3
35633 Lahnau
Phone: +49 6441 609-0
www.wiwa.de

Subsidiario WIWA de EE.UU.

WIWA LLC – USA, Canadá, America Latina
107 N. Main St.
P.O. Box 398, Alger, OH 45812
Tfno.: +1-419-757-0141
Fax: +1-419-549-5173
Gratis: +1-855-757-0141

www.wiwausa.com

WIWA (Taicang) Co., Ltd, China

No.11, East Qingdao Rd
Taicang City,
Jiangsu Province 215400,
Phone: +86 5 12 5354 8858
www.wiwa-china.com

AL RIDA Machines Equip.

Warehouse No. 14, Toufiq L Warehouse
Industrial Area 17, Sharjah U.A.E.
Phone: +971 6 5330100
Mobile: +971 50 1743128
E-mail: sales@alridamachines.com



WIWA FLEXIMIX 2 ATEX, electronic plural component spray equipment



WIWA DUOMIX, pneumatic plural component spray equipment



WIWA DUOMIX PU HX, hydraulic plural component spray equipment



WIWA DUOMIX 333 PFP ATEX, for intumescent fire protection material



WIWA HERKULES 333 GX, single feed (airless) spray equipment



WIWA VULKAN, pneumatic extrusion equipment

WIWA DUOMIX270 • 00050098.1 • EN • Images may include special accessories subject to extra costs • Errors and spelling mistakes and technical changes reserved! • 03/2017



WIWA DUOMIX 270
HIGH PRESSURE PLURAL COMPONENT SPRAY EQUIPMENT
FOR HEAVY DUTY COATINGS

SETTING THE NEW STANDARD IN POWER AND RELIABILITY

Electronic controls include potlife monitoring, flush program execution, mixing ratio memory and data recording with the **WIWA DATALOGGER**.

Optimized control panel provides ease of operation and conforms to the EU Machine directive with regard to the safety shut-off requirement.

Mixing takes place directly on the unit or in an external mixing block connected by a (heated) hose package up to 100m away

When dealing with products with extreme mixing ratios, several static mixers can be combined

Wireless and USB interface to access logged data

WIWA's new generation, low noise, oil free, anti-icing air motor provides a high pressure ratio and high volume output without pulsation

Supply pump for small or large containers

Optional: ATEX version for working in Ex zone areas

The new material pump design provides enhanced flow, resulting in longer life of the wear parts, while the mixing ratio can be changed in a matter of minutes by replacing the pumps, over 200 mixing ratios can be set up this way



Technical Data

Volumetric mixing ratio	1:1 to 10:1
Pressure ratio	20:1 to 80:1
Max. operating pressure	450 bar
Max. output per cycle	396 ccm
Max. output at 40 cycle	15,8 l

WIWA DUOMIX 270